



Hazardous Substance, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **Bostik Epoxy Bond (Resin)**

Synonyms:

Bostik Epoxy Bond (Resin), 5 mL tube
Bostik Epoxy Bond (Resin), 12 mL in a 24 mL dual barrel syringe

Mancode

311235
301841

Recommended use: Part A of a general purpose 2-part adhesive.

Supplier: Bostik Australia Pty Ltd
ABN: 79 003 893 838
Street Address: 51-71 High Street
Thomastown VIC 3074
Australia
Telephone: +613 9279-9333
Facsimile: +613 9279-9342

Emergency telephone number: 1800 033 111

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of NOHSC Australia.

Hazard Category:

Xi Irritant

Risk Phrase(s):

R36/37/38: Irritating to eyes, respiratory system and skin.
R43: May cause sensitisation by skin contact.

Safety Phrase(s):

S23: Do not breathe vapour.
S24/25: Avoid contact with skin and eyes.
S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.
S38: In case of insufficient ventilation, wear suitable respiratory equipment.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

Classified as a C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

Poisons Schedule (Aust): S5

This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.



3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO.	PROPORTION
4,4'-Isopropylidenediphenol	80-05-7	>60%
Ingredients determined to be non-hazardous	-	Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin contact: If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital.

Eye contact: If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Notes to physician: Treat symptomatically. Effects may be delayed.

5. FIRE-FIGHTING MEASURES

Specific hazards: Combustible liquid.

Fire fighting further advice: On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.



LARGE SPILLS

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: Not applicable.

7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

Classified as a C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC Australia).

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC: 1005 (1994)]" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Natural ventilation should be adequate under normal use conditions.

Personal protection equipment: OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.

Wear overalls, chemical goggles and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using. If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Viscous pale yellow liquid, with slight odour.

Solubility:	Insoluble in water.
Specific Gravity (20 °C):	1.16
Relative Vapour Density (air=1):	N Av
Vapour Pressure (20 °C):	N Av

Material Safety Data Sheet



Flash Point (°C):	>150
Flammability Limits (%):	N App
Autoignition Temperature (°C):	>300
Melting Point/Range (°C):	N Av
Boiling Point/Range (°C):	>200
pH:	N App
Viscosity (30°C):	6,000-8,000 cps

(Typical values only - consult specification sheet)
N Av = Not available N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible Materials: Oxidising agents, acids and alkalis.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: Reacts with acids and alkalis.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material is irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin will result in irritation. A skin sensitizer. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Eye contact: An eye irritant.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Long Term Effects: No information available for product.

Acute toxicity / Chronic toxicity

No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Material Safety Data Sheet



Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Refer to State/Territory Land Waste Management Authority.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

Poisons Schedule (Aust): S5

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Literary reference

This Material Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd on behalf of its client.

Reason(s) For Issue: First Issue

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Bostik Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.



NON-Hazardous Substance, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **Bostik Epoxy Bond (Hardener)**

Synonyms:

Bostik Epoxy Bond (Hardener), 5 mL

Bostik Epoxy Bond (Hardener), 12 mL in a 24 mL dual barrel syringe

Mancode

311235

301841

Recommended use: Part B of a 2-part general purpose adhesive.

Supplier: Bostik Australia Pty Ltd

ABN: 79 003 893 838

Street Address: 51-71 High Street
Thomastown VIC 3074
Australia

Telephone: +613 9279-9333

Facsimile: +613 9279-9342

Emergency telephone number: 1800 033 111

2. HAZARDS IDENTIFICATION

Based on available information, this material is not classified as hazardous according to criteria of NOHSC Australia.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

Classified as a C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

Poisons Schedule (Aust): S5

This material is a Scheduled Poison S and must be stored, maintained and used in accordance with the relevant regulations.

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO.	PROPORTION
Ingredients determined to be non-hazardous	-	Balance
		<hr/> 100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Notes to physician: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Specific hazards: Combustible liquid.

Fire fighting further advice: On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: Not applicable.

7. HANDLING AND STORAGE

Handling: Avoid eye contact and repeated or prolonged skin contact.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

Material Safety Data Sheet



Classified as a C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC Australia).

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC: 1005 (1994)]" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Natural ventilation should be adequate under normal use conditions.

Personal protection equipment: OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.

Wear overalls, chemical goggles and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using. If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Viscous light yellow liquid with mercaptan odour.

Solubility:	Insoluble
Specific Gravity (20 °C):	1.13
Relative Vapour Density (air=1):	N Av
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	257
Flammability Limits (%):	N Av
Autoignition Temperature (°C):	N Av
Melting Point/Range (°C):	N App
Boiling Point/Range (°C):	N Av
pH:	N App
Viscosity (30°C):	10,000-15,000 cps

(Typical values only - consult specification sheet)

N Av = Not available

N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible Materials: Oxidising agents.

Material Safety Data Sheet



Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No information available.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin may result in irritation.

Eye contact: May be an eye irritant.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Long Term Effects: No information available for product.

Acute toxicity / Chronic toxicity

No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Refer to State/Territory Land Waste Management Authority.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Material Safety Data Sheet



AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

Poisons Schedule (Aust): S5

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Literary reference

This Material Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd on behalf of its client.

Reason(s) For Issue: First Issue

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Bostik Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.